

# ◆ WEATHERWASH ◆

THE NATURAL WAY TO WEATHER WOOD

Weatherwash Varnish is a non-yellowing, water-based sealer. Weatherwash Varnish is a high quality, pre-catalyzed conversion wood sealer which provides maximum protection for Weatherwash stained wood. Weatherwash Varnishes will look beautiful on Weatherwash stained wood whether applied with a brush or a professional spray gun. This formula is perfect for the protection of all raw or Weatherwash stained wood.

**USE** For use on cabinetry, furniture and millwork.

**SPECIES** For use on any wood species.

- 💧 Water-Based
- 🔪 Sheen Dead Flat
- 😊 Easy Clean Up
- 👉 Anti Yellowing
- 🏠 Commercial & Residential



## DIRECTIONS

**WOOD PREP** Ensure wood is free of dust, dirt, conditioners and oils. Remove any sanding dust with tack cloth. Unfinished surfaces should be sanded with 120 grit prior to applying varnish.

**PRODUCT PREP PREPARATION** Stir well.

**COVERAGE** 1 Quart treats 100 SQ FT of smooth wood.

**APPLICATION** Varnish may be applied with a roller, sprayer or brush. Product looks milky when first applied but dries clear. To avoid bubbles, do not over brush. Use a damp sponge brush to remove any bubbles on the wood's surface. For superior protection, apply up to three coats of varnish. Always apply in a well-ventilated area. When using a spray gun, varnish may be thinned up to 15% with water. Do not apply in temperatures below 55°F.

**DRYING TIME** Apply 2-3 coats for superior protection, especially in high traffic or water-exposed areas. Apply 2nd coat within 4 hours of applying 1st coat or wait 48 hours

**CLEAN UP** Easy soap and water clean up.