

# WEATHERWASH COATINGS SDS: CLEAR MAINTENANCE OIL

## M A T E R I A L   S A F E T Y   D A T A   S H E E T

### SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WEATHERWASH CLEAR MAINTENANCE OIL

IDENTIFICATION NUMBER: LT-08-146

COMPANY: WW CO. LLC

SIZES: 32 OZ, 128 OZ, 640 OZ

DISTRIBUTOR: WW CO. LLC 1299 W 635 S OREM UT 84058

CHEMICAL INFORMATION: [SUPPORT@WEATHERWASHCOATINGS.COM](mailto:SUPPORT@WEATHERWASHCOATINGS.COM)

CHEMTREC 24HR EMERGENCY TELEPHONE 800-424-9300

### SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	HYDROCARBON MIXTURE	64741-65-2	75.0 %
02	Long Oil Alkyd		25.0 %
03	Hydrocarbon Mixture	64742-88-7	5.0 %
04	Xylene	1330-20-7	5.0 %
05	Paraffin wax dispersion in ms		1.0 %

ITEM	EXPOSURE LIMITS				COMPANY TLV-TWA	SKIN
	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING		
01	100	100	100			NO
02	N.E.	N.E.	N.E.	N.E.	N.E.	NO
03	N.E.	N.E.	N.E.	N.E.	100ppm	NO
04	100 ppm	150 ppm	100 ppm	N.E.	100 ppm	NO
05	N.E.	N.E.	N.E.	N.E.	N.E.	NO

(See Section 16 for abbreviation legend)

### SECTION 3 - HAZARDS IDENTIFICATION

\*\*\* EMERGENCY OVERVIEW \*\*\*: Harmful if swallowed or inhaled. On overexposure, could cause (target organ or system) damage. (e.g., lung, nervous system, blood disorders, liver, kidney, immune system, cardiovascular system, thyroid, testicular, ovarian, etc.).

# WEATHERWASH COATINGS SDS: CLEAR MAINTENANCE OIL

Product: LT-08-146

Preparation Date: 07/28/17

Page 2

## SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION: Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure may cause nervous system damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Misuse of this product may be harmful or fatal.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION  
INGESTION EYE CONTACT

## SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and shoes. Do not reuse until cleaned.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

## SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 145 F

LOWER EXPLOSIVE LIMIT: 1.0 %  
UPPER EXPLOSIVE LIMIT: 6.6 %

AUTOIGNITION TEMPERATURE:

# WEATHERWASH COATINGS SDS: CLEAR MAINTENANCE OIL

Product: LT-08-146

Preparation Date: 07/28/17

Page 3

## SECTION 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Ventilate area. Absorb spill with suitable absorbent material, then place in a chemical waste container. If large spill, dike area and call spill response team. Notify appropriate state and local agencies.

## SECTION 7 - HANDLING AND STORAGE

HANDLING: wash thoroughly after handling.

STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use. Do not weld, heat or drill on or near container; even emptied containers can contain explosive vapors. Store away from strong oxidizing agents in a cool, dry place with appropriate ventilation.

## SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment.

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace

# WEATHERWASH COATINGS SDS: CLEAR MAINTENANCE OIL

Product: LT-08-146

Preparation Date: 07/28/17

Page 4

## SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

conditions warrant a respirator's use.

**SKIN PROTECTION:** Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.

**OTHER PROTECTIVE EQUIPMENT:** Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment.

**HYGIENIC PRACTICES:** Always wash hands before eating, drinking, or smoking. Remove contaminated clothing and wash before reuse. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	: 281 - 406 F	VAPOR DENSITY	: Is heavier than air
ODOR	:	ODOR THRESHOLD	:
APPEARANCE	:	EVAPORATION RATE:	Is slower than Butyl Acetate
SOLUBILITY IN H2O	:	SPECIFIC GRAVITY:	0.8084
FREEZE POINT	:	pH @ 0.0 %	:
VAPOR PRESSURE	:	VISCOSITY	:
PHYSICAL STATE	:		
VOLATILE BY VOLUME: 99.1%			
COEFFICIENT OF WATER/OIL DISTRIBUTION:			

(See Section 16 for abbreviation legend)

## SECTION 10 - STABILITY AND REACTIVITY

**CONDITIONS TO AVOID:** Avoid heat, sparks, and open flame. Avoid contact with alkalies, aqueous acids, amines, and acidic alcohols.

**INCOMPATIBILITY:** Avoid contact with strong oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide.

**HAZARDOUS POLYMERIZATION:** will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

Product: LT-08-146

Preparation Date: 07/28/17

Page 5

SECTION 11 - TOXICOLOGICAL PROPERTIES

TOXICOLOGICAL INFORMATION: No Information.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Refer to local, county, state and federal storm water and air quality regulations.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: If discarded, this material and its containers may have to be treated as hazardous waste based on the characteristics of ignitability as defined under Federal RCRA regulations (40 CFR 261). Disposal of this material may require compliance with applicable labeling, packaging, and record keeping standards. Extreme care should be taken to ensure that it is disposed of only in a facility permitted for disposal of hazardous waste.

SECTION 14 - TRANSPORTATION INFORMATION

- 14.1 UN Number: 1263
- 14.2 UN Proper Shipping Name: Paint-related material
- 14.3 Transport Hazard Class: 3
- 14.4 Packaging Group: III
- 14.5 Environmental Hazards: n/a

# WEATHERWASH COATINGS SDS: CLEAR MAINTENANCE OIL

## SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD    CHRONIC HEALTH HAZARD    FIRE HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
Xylene	1330-20-7	5.0 %

U.S. STATE REGULATIONS: AS FOLLOWS -

CALIFORNIA PROPOSITION 65:

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

## SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 2            FLAMMABILITY: 1            REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 07/27/17

VOLATILE ORGANIC COMPOUNDS (VOCs): 4.95 lbs/gal,    593 grams/ltr

LEGEND:    N.A. - Not Applicable, N.E. - Not Established,  
              N.D. - Not Determined