

◆ WEATHERWASH ◆

THE NATURAL WAY TO WEATHER WOOD

Weatherwash Varnish is a non-yellowing, water-based sealer. Weatherwash Varnish is a high quality, pre-catalyzed conversion wood sealer which provides maximum protection for Weatherwash stained wood. Weatherwash Varnishes will look beautiful on Weatherwash stained wood whether applied with a brush or a professional spray gun. This formula is perfect for the protection of all raw or Weatherwash stained wood.

USE For use on cabinetry, furniture and millwork.

SPECIES For use on any wood species.

- 💧 Water-Based
- 🔪 Sheen Dead Flat
- 😊 Easy Clean Up
- 👉 Anti Yellowing
- 🏠 Commercial & Residential



DIRECTIONS

WOOD PREP Ensure wood is free of dust, dirt, conditioners and oils. Remove any sanding dust with tack cloth. Unfinished surfaces should be sanded with 120 grit prior to applying varnish.

PRODUCT PREP PREPARATION Stir well.

COVERAGE 1 Quart treats 100 SQ FT of smooth wood.

APPLICATION Varnish may be applied with a roller, sprayer or brush. Product looks milky when first applied but dries clear. To avoid bubbles, do not over brush. Use a damp sponge brush to remove any bubbles on the wood's surface. For superior protection, apply up to three coats of varnish. Always apply in a well-ventilated area. When using a spray gun, varnish may be thinned up to 10% with water. Do not apply in temperatures below 55°F.

DRYING TIME Apply 2-3 coats for superior protection, especially in high traffic or water-exposed areas. Apply 2nd coat within 4 hours of applying 1st coat or wait 48 hours

CLEAN UP Easy soap and water clean up.